



# Results of Preliminary Competency Testing of Paste Backfill Derived from Uranium Leach By-Products

Troy Boisjoli, VP Operations & Project Development

*October 18<sup>th</sup>, 2018*



# Forward Looking Statement

## Information Contained in this Presentation

This presentation is a summary description of NexGen Energy Ltd. (“**NexGen**” or the “**Company**”) and its business and does not purport to be complete. This presentation is not, and in no circumstances is to be construed as a prospectus, advertisement or a public offering of securities. No securities regulatory authority or similar authority has reviewed or in any way passed upon the document or the merits of the Company’s securities and any representation to the contrary is an offence.

Except where otherwise indicated, the information contained in this presentation has been prepared by NexGen and there is no representation or warranty by NexGen or any other person as to the accuracy or completeness of the information set forth herein. This presentation includes information on adjacent properties that was obtained from various publicly available sources referred to herein and the accuracy and completeness of such information has not been verified by NexGen. Except as otherwise stated, information included in this presentation is given as of the date hereof. The delivery of this presentation shall not imply that the information herein is correct as of any date after the date hereof.

## Forward-Looking Information

The information contained herein contains “forward-looking statements” within the meaning of the United States Private Securities Litigation Reform Act of 1995 and “forward-looking information” within the meaning of applicable Canadian securities legislation. “Forward-looking information” includes, but is not limited to, statements with respect to the activities, events or developments that the Company expects or anticipates will or may occur in the future, including, without limitation, the completion of the technical report in support of the PEA. Generally, but not always, forward-looking information and statements can be identified by the use of words such as “plans”, “expects”, “is expected”, “budget”, “scheduled”, “estimates”, “forecasts”, “intends”, “anticipates”, or “believes” or the negative connotation thereof or variations of such words and phrases or state that certain actions, events or results “may”, “could”, “would”, “might” or “will be taken”, “occur” or “be achieved” or the negative connotation thereof.

Forward-looking information and statements are based on the then current expectations, beliefs, assumptions, estimates and forecasts about NexGen’s business and the industry and markets in which it operates. Forward-looking information and statements are made based upon numerous assumptions, including among others, the results of planned exploration activities are as anticipated, the price of uranium, the cost of planned exploration activities, that financing will be available if and when needed and on reasonable terms, that third party contractors, equipment, supplies and governmental and other approvals required to conduct NexGen’s planned exploration activities will be available on reasonable terms and in a timely manner and that general business and economic conditions will not change in a material adverse manner. Although the assumptions made by the Company in providing forward-looking information or making forward-looking statements are considered reasonable by management at the time, there can be no assurance that such assumptions will prove to be accurate.

Forward-looking information and statements also involve known and unknown risks and uncertainties and other factors, which may cause actual results, performances and achievements of NexGen to differ materially from any projections of results, performances and achievements of NexGen expressed or implied by such forward-looking information or statements, including, among others, negative operating cash flow and dependence on third party financing, uncertainty of the availability of additional financing, the risk that pending assay results will not confirm previously announced preliminary results, imprecision of mineral resource estimates, the appeal of alternate sources of energy and sustained low uranium prices, aboriginal title and consultation issues, exploration risks, reliance upon key management and other personnel, deficiencies in the Company’s title to its properties, uninsurable risks, failure to manage conflicts of interest, failure to obtain or maintain required permits and licenses, changes in laws, regulations and policy, competition for resources and financing, or other approvals, and other factors discussed or referred to in the Company’s Annual Information Form dated March 31, 2017 under “Risk Factors”.


Although the Company has attempted to identify important factors that could cause actual results to differ materially from those contained in the forward-looking information or implied by forward-looking information, there may be other factors that cause results not to be as anticipated, estimated or intended.

There can be no assurance that forward-looking information and statements will prove to be accurate, as actual results and future events could differ materially from those anticipated, estimated or intended. Accordingly, readers should not place undue reliance on forward-looking statements or information. The Company undertakes no obligation to update or reissue forward-looking information as a result of new information or events except as required by applicable securities laws.

# Presentation Outline

- Background
  - NexGen Energy
  - Rook I property
  - Arrow deposit
- Paste backfill study
  - Purpose
  - Objectives
  - Criteria
  - Methodology
  - Results
  - Conclusions
- Next steps

# Background NexGen Energy



- Canadian uranium exploration and development company
  - 380 km<sup>2</sup> mineral lease
  - Focused in the Southwest Athabasca Basin
  - Operations headquarters in Saskatoon
- Rook I
  - Flagship property
  - Patterson Lake area
  - 150 km north of La Loche  
600 km north of Saskatoon



# Background Rook I



- Exploration since 2012
  - Air and land-based
  - >300,000 m drilled
- Supported by advanced exploration camp
- Arrow deposit
  - Discovered in 2014


# Background Arrow Deposit



- Location
  - North of existing camp
  - 14 km east of Highway 955
- Basement hosted deposit
  - Entirely within crystalline basement rock
- Land-based
  - Remains open at strike and depth




# Arrow Deposit Setting



# Arrow Deposit Results to Date

- Largest undeveloped uranium deposit in Saskatchewan
- Evaluating technical, economic & environmental feasibility
  - PEA (July 2017)
  - PFS (Q4 2018)
- Strong potential for mine and mill development

Classification	Resource Estimate (million tonnes)	Grade (% $U_3O_8$ )	Total $U_3O_8$ (million pounds)
Indicated	1.18	6.88	179.5
Inferred	4.25	1.30	122.1






# Rook I

## Project Development

- Mine
  - Conventional long-hole stope, drill & blast
  - Shaft access
  - 1,200 – 1,500 tonnes per day
- Mill
  - Conventional mill w/ acid strip
  - 29 million lbs  $U_3O_8$  per year
  - 15 year mine life
- Small surface footprint
  - 132 hectares
- **Novel approach to processing and disposing mill waste streams**

# Arrow Deposit Mill Solid Waste Management




- Mill solid waste streams
  - Neutralized leaching residues
  - Gypsum residues
  - Water treatment precipitates
- Paste plant processing
  - Wastes processed into cemented paste within the mill
  - Mixed with binders and water
  - Engineered to meet prescribed criteria for strength, rheology, and stability



# Cemented Paste Backfill

## Alternative Uranium Tailings Management



- Mine waste return via pipeline
  - Pumped underground
- Storage options
  - Stope backfill
    - Utilization of cemented paste backfill in mined-out stopes to support on-going operations
  - Underground Processed Waste Management Facility
    - Purpose-built, dedicated processed waste management facility

# Cemented Paste Backfill

## Alternative Uranium Tailings Management

- Proven approach
  - Well understood, broadly used in other mining sectors
  - Technology readily available and demonstrated
- Integration with operations
  - Structural support for mining operations
  - Return residual solid waste back underground
- Environmental performance
  - Reduced surface footprint
  - Reduced potential contaminant mobility
  - No long-term management of surface facility
  - Allows for progressive decommissioning of process waste during operation



# Cemented Paste Backfill Pilot-Scale Characterization Study

- Evaluation of technical feasibility
  - Proof-of-concept
  - Incorporated into metallurgical test-work
- Designed and directed by subject matter experts
  - Wood Canada Limited
  - Saskatchewan Research Council
- Study lead
  - Corina-Maria Aldea, PhD, P. Eng, FACI
    - Test program development, paste backfill design and oversight
- Laboratory testing leads
  - Jack Zheng PhD, P. Eng & Tim Oleniuk P. Eng
    - Paste backfill preparation and testing



# Cemented Paste Backfill

## Study Objectives

- Neutralized leach residues
  - Physical: establish ability to form a stable, competent, and pumpable paste
  - Chemical: evaluate acid generating potential and chemical compatibility with the additives
- Cemented Paste backfill
  - Identify suitable binders
  - Identify appropriate mix design
  - Evaluate suitability of using process water in the paste mix
  - Evaluate paste pumpability, in-situ strength, long-term durability



# Cemented Paste Backfill

## Study Criteria

Category	Property	Description	Value	Unit
General Criteria	Paste Pumpability/ Mix Design	% Fines (<20 µm)	15 – 20	%
Project-specific Targets	Paste Pumpability	Slump	203 - 229	mm
	28 day Unconfined Compressive Strength	High-strength backfill	1.5	MPa
		Regular strength backfill	1	MPa
		Low strength backfill	0.5	MPa

# Cemented Paste Backfill

## Methodology: Neutralized Leach Residues

- Sample preparation
  - Sample collection
    - Neutralized washed residues from pilot-scale leaching circuit
    - Decanted and dried to ~80% - 85% solids
  - Process water characterization
    - Collected and analyzed to evaluate suitability for use in paste mix (potential to reduce freshwater consumption)
- Testing
  - Physical
    - Sieve analysis, laser particle diffraction, specific gravity
  - Chemical
    - Full chemical analysis, acid-base accounting
  - Mineralogical
    - X-ray diffraction

# Cemented Paste Backfill

## Methodology: Paste

- Paste mix preparation
  - Laboratory scale batches
  - Portland cement & granulated blast furnace slag used as binders


Ingredient	Unit	MO	M1	M2	M3	M4	M5	M6
Dry Tailings	%	71	62	61	59	61	62	61
Process water	%	29	34	34	34	35	33	32
Portland Cement	%	0	4	5	7	2	2.5	3.5
Slag	%	0	0	0	0	2	2.5	3.5

- Testing
  - Rheology
    - Cylinder and cone slump, slump flows, shear rate, shear stress, viscosity
  - Strength
    - Unconfined compressive strength
    - 7, 14, 28, 56, 90 day aging tests



# Cemented Paste Backfill

## Study Results: Particle Distribution




# Cemented Paste Backfill Study Results: Slump



*Photo credit: Wood Canada*

# Cemented Paste Backfill Study Results: Strength





# Cemented Paste Backfill

## Study Conclusions: Leach Residues

- Creation of a stable, competent, and pumpable paste
  - Workable paste product can be achieved using neutralized leaching residues
  - High fines content requires additional consideration
- Chemically compatibility with the additives
  - No adverse or unexpected chemical reactions with Portland cement or slag

# Cemented Paste Backfill

## Study Conclusions: Paste Backfill

- Optimal mix design
  - ~30% water
  - ~60% neutralized leach residues
  - ~5 – 7% binder
- Process water as a component of the paste mix
  - No impact on condition or quality of paste product
- Paste pumpability
  - Established pumpability of paste product
  - Ideal moisture content identified, evaluate options for fines fraction
- Strength of paste
  - High strength achieved
  - Incorporation of binders to meet strength specifications
  - Strength increases during the setting period

# Cemented Paste Backfill

## Next Steps

- Paste mix design
  - Investigate local binder sources
  - Optimize binder dosage rates
- Other process waste streams
  - Gypsum residues
  - Water treatment precipitates
- Processed waste product characterization
  - Radiological properties
  - Long-term leaching potential
- Paste plant, transfer and storage
  - Design consideration and plant capacity, pump and transfer system, placement strategy and design

# Questions

